



Designer Manufacturer

IL 16 - 20 - 30

Industrial protective cabinet for laser printer

Characteristics:

- The body of the cabinet is a thermoplastic form, meaning the side panels and rear are a single unit;
- Panels painted (RAL 7037), 10 mm-thick composite material;

Rear panel:

- Cable gland diameter 80 mm.

Side panels:

- Two air inlets fitted with anti-dust filters.

HANDLING:

Front panel:

- Front access to printer:
- Thermoplastic fold-down flap mounted on piano-style hinges and held shut by two latches.

Upper face:

- 6 mm-thick transparent PMMA, mounted on two polyamide hinges.
- Assisted opening using pneumatic rams to hold the cover open while work is done inside the printer;
- Cover closes by slotting into drop-down flap and against side seals.

Option - side panel :

VENTILATION: The ventilation and suction systems:

- draw in and filter air, create positive pressure in the internal volume;
- discharge air when the cabinet is opened, thereby creating an active barrier that prevents the entry of dust.
- Two ECA (fans placed behind a filtered grille) attached to the rear panel;
- Computer equipment power-up coupled to cabinet power-up (fans) using a switch;

Advantages:

- Ergonomically designed cabinet
- Optimum permanent protection
- Guaranteed leaktight dust seal


• Food grade version available: AL 16 - 20 - 30



IL DIMENSIONS (mm):			IL DIMENSIONS (mm):			IL DIMENSIONS (mm):		
	IL 16		IL 20		IL 30			
Overall external	W 500 x D 600 x H 500 mm	Overall external	W 580 x D 700 x H 600 mm	Overall external	W 700 x D 600 x H 600 mm			
Usable internal	W 480 x D 520 x H 470 mm	Usable internal	W 560 x D 620 x H 570 mm	Usable internal	W 680 x D 520 x H 570 mm			



IL 20 with LEGS option SINGLE UNIT and TAV LASER and option ECA



IL 16 with drop-down flap open on front panel, PRINTER SUPPORT option and Option L2



IL 20 with option LEGS SINGLE UNIT and TAV LASER and ECA



Fixed and mobile workstations

OVERVIEW OF OPTIONS

*The Industrial protection system
for your laser printers*



SINGLE UNIT LEGS option

- Steel legs painted grey RAL 7035, height 680 mm.




KDL option

- Opening cable gland system designed to allow cables to be connected without having to remove their end pieces;
- The gland glands are in two sections which hold the cables in leaktight seals;
- Generally fitted to the right hand side panel, to ensure the cabinet remains leaktight.



MANUAL REGULATOR option

- Cabinet connected to dry air network via manual regulator used to create positive pressure inside the cabinet and avoid penetration of dust, particles, etc.



*Option L
2: Light +
Guide*

PAPER EXIT options

- Option L2 (*Light + Guide*): Cover cut-out (top panel) and paper exit guide
- TAV LASER option: Unbreakable polycarbonate window, dimensions W 250 x H 190 mm;

*TAV LASER
option:*



Additional options:

- RCA: Possible to add heating system on request

LM REALISATIONS S.A.S

ZI du Bas Pontet - 19, rue Jules Ferry - 69360 Saint Symphorien d'Ozon - FRANCE
Tel. 33 (0)4 78 02 84 93 - Fax 33 (0)4 78 02 17 03 - infos@lm-realisations.fr

www.lm-realisations.com

