Fixed and mobile workstations

LCD PROTECTION IP65 LEAKTIGHT @



Foodgrade protective cabinet for LCD screens

Characteristics:

- · Protects flatscreen monitors from splashes, washing, dust, temperature changes, cold,
- The rear & sides of the cabinet body is a single, thermoplastic form;
- Front cover in transparent thermoplastic PMMA, 6 mm thick, slides upwards on runners for access to the screen;
- The body is a composite material, 10 mm thick, making it watertight;
- · Protected ventilation grilles on either side;
- Thermoformed panels making up the cabinet;
- · Smooth, easy-to-clean surface;
- · Cabinet can be wall-mounted:
- Screen mounting plate within the cabinet;
- Access to screen by a handle, screwed onto the casing on the top of the cabinet;
- Connectivity: KDL, screwed onto the cabinet base:
 - System of opening cable glands to allow cables to be passed into the cabinet without having to remove connectors or cut the cables themselves;
 - The cable glands are in two sections which clamp onto the cables within the seals.

The perfect solution to protect your LCD screens

DIMENSIONS - LCD PROTECTION IP 65 LEAKTIGHT (in mm):

External

W 500 x D 100 x H 500 mm

Usable internal

W 480 x D 74 x H 480 mm

The various uses for LCD PROTECTION IP65 LEAKTIGHT

Also available as a LOGIRACK INOX (stainless steel) version with LCD PROTECTION IP65 LEAKTIGHT





LM REALISATIONS S.A.S.

ZI du Bas Pontet - 19, rue Jules Ferry - 69360 Saint Symphorien d'Ozon - FRANCE Tel. 33 (0)4 78 02 84 93 - Fax 33 (0)4 78 02 17 03 - infos@lm-realisations.fr

www.lm-realisations.com

